

## Author Index,<sup>1</sup> 1991

### *The Telecommunications and Data Acquisition Progress Report*

*42-105, January–March, May 15, 1991*

*42-106, April–June, August 15, 1991*

*42-107, July–September, November 15, 1991*

*42-108, October–December, February 15, 1992*

#### **Abdel-Ghaffar, K.**

- 42-107 Some Partial-Unit-Memory Convolutional Codes, pp. 57–72.  
R. J. McEliece and G. Solomon

#### **Arbel, D.**

- 42-106 Design and Testing of an Active Quenching Circuit for an Avalanche Photodiode Photon Detector, pp. 102–110.  
J. A. Schwartz

#### **Abdel-Hamid, T.**

- 42-108 Software-Engineering Process Simulation Model (SEPS), pp. 165–185.  
See Lin, C. Y.

#### **Arnold, S.**

- 42-108 Node Synchronization Schemes for the Big Viterbi Decoder, pp. 196–200.  
See Cheung, K.-M.

#### **Alvarez, L. S.**

- 42-106 Efficiency Calibration of the DSS 13 34-Meter Diameter Beam Waveguide Antenna at 8.45 and 32 GHz, pp. 283–297.  
See Slobin, S. D.
- 42-106 Initial Pointing Calibrations for the DSS 13 34-Meter Beam-Waveguide Antenna, pp. 188–204.

#### **Asmar, S.**

- 42-105 Radio Science Ground Data System for the Voyager–Neptune Encounter—Part I, pp. 109–127.  
See Kursinski, E. R.

#### **Bartos, R. D.**

- 42-108 Dynamic Modeling of the Servovalves Incorporated in the Servo Hydraulic System of the 70-Meter DSN Antennas, pp. 222–234.

---

<sup>1</sup> In the case of joint authorship, the reader is referred to the citation under the first author, where all the authors of the article are listed.

- Bathker, D. A.**
- 42-105 Gaussian Beam and Physical Optics Iteration Technique for Wideband Beam Waveguide Feed Design, pp. 128–135.  
See Veruttipong, W.
- Bautista, J. J.**
- 42-106 Performance of a High  $T_c$  Superconducting Ultra-Low Loss Microwave Stripline Filter, pp. 60–65.  
G. Ortiz, C. Zahopoulos, S. Sridhar, and M. Lanagan
- Bevan, R.**
- 42-106 The Advanced Receiver II Telemetry Test Results at Goldstone, pp. 119–131.  
See Sadr, R.
- Bienkiewicz, B.**
- 42-108 Pointing-Error Simulations of the DSS-13 Antenna Due to Wind Disturbances, pp. 109–134.  
See Gawronski, W.
- Blewitt, G.**
- 42-108 A Demonstration of Centimeter-Level Monitoring of Polar Motion With the Global Positioning System, pp. 1–9.  
See Lindqwister, U. J.
- Briggs, H. C.**
- 42-107 Mark IVA Antenna Control System Data Handling Architecture Study, pp. 96–103.  
D. B. Eldred
- Britcliffe, M. J.**
- 42-106 Efficiency Calibration of the DSS 13 34-Meter Diameter Beam Waveguide Antenna at 8.45 and 32 GHz, pp. 283–297.  
See Slobin, S. D.
- Brockman, M. H.**
- 42-106 A Carrier-Arraying Demonstration at Goldstone for Receiving Pioneer 11 Signals, pp. 307–334.  
See Pham, T. T.
- Brown, R. D.**
- 42-108 Using Single Buffers and Data Reorganization to Implement a Multi-Megasample Fast Fourier Transform, pp. 294–306.
- Buchanan, H. R.**
- 42-106 Modeling Preparation Costs for Space Missions by Using Major Cost Drivers, pp. 404–415.  
See Sherif, J. S.
- Charny, B.**
- 42-107 A 640-MHz 32-Megachannel Real-Time Polyphase-FFT Spectrum Analyzer, pp. 132–140.  
See Zimmerman, G. A.
- Chen, J. C.**
- 42-105 Gaussian Beam and Physical Optics Iteration Technique for Wideband Beam Waveguide Feed Design, pp. 128–135.  
See Veruttipong, W.
- 42-105 X-/Ka-Band Dichroic Plate Design and Grating Lobe Study, pp. 21–30.
- 42-106 DSS 13 Phase II Pedestal Room Microwave Layout, pp. 298–306.  
See Cwik, T.
- Cheung, K.-M.**
- 42-105 Integer Cosine Transform for Image Compression, pp. 45–53.  
F. Pollara and M. Shahshahani
- 42-106 Frame Error Rate of the NASA Concatenated Coding System, pp. 183–187.  
See Swanson, L.

- 42-107 A Comparison of the Fractal and JPEG Algorithms, pp. 21–26.  
See Shahshahani, M.
- 42-108 Node Synchronization Schemes for the Big Viterbi Decoder, pp. 186–200.  
L. Swanson and S. Arnold
- Clauss, R.**
- 42-108 DSN  $G/T_{op}$  and Telecommunications System Performance, pp. 271–278.  
See Stelzried, C.
- Clements, P. A.**
- 42-108 An Assembly to Provide a Time Reference for the JPL Network Operations Control Center, Real-Time pp. 214–221.  
J. G. Lopez and M. J. Kelley
- Collins, O.**
- 42-107 A Minimalist Approach to Receiver Architecture, pp. 27–35.
- 42-107 Determinate-State Convolutional Codes, pp. 36–56.  
M. Hizlan
- Cormier, R.**
- 42-108 250-kW CW Klystron Amplifier for Planetary Radar, pp. 201–213.  
A. Mizuhara
- Cowles, K.**
- 42-105 Site Comparison for Optical Visibility Statistics in Southern California, pp. 31–40.
- 42-108 Alignment of the Atmospheric Visibility Monitoring Telescope, pp. 79–83.  
D. Erickson
- Cwik, T.**
- 42-106 DSS 13 Phase II Pedestal Room Microwave Layout, pp. 298–306.
- Dick, G. J.**
- 42-107 A Receiver Design for the Superconducting Cavity-Maser Oscillator, pp. 1–11.  
See Wang, R. T.
- 42-108 A High-Performance  $Hg^+$  Trapped Ion Frequency Standard, pp. 10–18.  
See Prestage, J. D.
- Edwards, C. D.**
- 42-108 Position Determination of a Lander and Rover at Mars With Earth-Based Differential Tracking, pp. 279–293.  
See Kahn, R. D.
- Eldred, D. B.**
- 42-107 Mark IV A Antenna Control System Data Handling Architecture Study, pp. 96–103.  
See Briggs, H. C.
- Erickson, D.**
- 42-108 Alignment of the Atmospheric Visibility Monitoring Telescope, pp. 79–83.  
See Cowles, K.
- Estefan, J. A.**
- 42-106 Precise Orbit Determination of High-Earth Elliptical Orbiters Using Differenced Doppler and Range Measurements, pp. 1–22.
- Flanagan, M. J.**
- 42-107 The Behavior of Quantization Spectra as a Function of Signal-to-Noise Ratio, pp. 155–168.

- Folkner, W. M.**
- 42-108 Position Determination of a Lander and Rover at Mars With Earth-Based Differential Tracking, pp. 279–293.  
See Kahn, R. D.
- Garyantes, M. F.**
- 42-107 A 640-MHz 32-Megachannel Real-Time Polyphase-FFT Spectrum Analyzer, pp. 132–140.  
See Zimmerman, G. A.
- Franco, M. M.**
- 42-105 A Portable X-Band Front-End Test Package for Beam-Waveguide Antenna Performance Evaluation—Part II: Tests on the Antenna, pp. 54–68.  
See Otoshi, T. Y.
- 42-106 A Portable Ka-Band Front-End Test Package for Beam-Waveguide Antenna Performance Evaluation—Part I: Design and Ground Tests, pp. 249–265.  
See Otoshi, T. Y.
- 42-106 A Portable Ka-Band Front-End Test Package for Beam-Waveguide Antenna Performance Evaluation—Part II: Tests on the Antenna, pp. 266–282.  
See Otoshi, T. Y.
- 42-106 Efficiency Calibration of the DSS 13 34-Meter Diameter Beam Waveguide Antenna at 8.45 and 32 GHz, pp. 283–297.  
See Slobin, S. D.
- 42-107 A Portable Ku-Band Front-End Test Package for Beam-Waveguide Antenna Performance Evaluation, pp. 73–80.  
See Otoshi, T. Y.
- 42-108 The Electrical Conductivities of the DSS-13 Beam-Waveguide Antenna Shroud Material and Other Antenna Reflector Surface Materials, pp. 154–164.  
See Otoshi, T. Y.
- Gawronski, W.**
- 42-105 Elevation Control System Model for the DSS 13 Antenna, pp. 83–108.  
J. A. Mellstrom
- 42-106 Modeling and Simulations of the DSS 13 Antenna Control System, pp. 205–248.  
J. A. Mellstrom
- 42-108 Pointing-Error Simulations of the DSS-13 Antenna Due to Wind Disturbances, pp. 109–134.  
B. Bienkiewicz and R. E. Hill
- Goldstein, R. M.**
- 42-105 Orbital Debris Radar Instrumentation, pp. 146–148.  
L. W. Randolph
- Gray, D. L.**
- 42-106 ΔVLBI Data Performance in the Galileo Spacecraft Earth Flyby of December 1990, pp. 335–352.
- Grimm, M. J.**
- 42-107 A 640-MHz 32-Megachannel Real-Time Polyphase-FFT Spectrum Analyzer, pp. 132–140.  
See Zimmerman, G. A.
- Freedman, A. P.**
- 42-105 Combining GPS and VLBI Earth-Rotation Data for Improved Universal Time, pp. 1–12.
- 42-108 A Demonstration of Centimeter-Level Monitoring of Polar Motion With the Global Positioning System, pp. 1–12.  
See Lindqwister, U. J.
- Gulkis, S.**
- 42-107 Polyphase-Discrete Fourier Transform Spectrum Analysis for the Search for Extraterrestrial Intelligence Sky Survey, pp. 141–154.  
See Zimmerman, G. A.

- Hill, R. E.**
- 42-108 Pointing-Error Simulations of the DSS-13 Antenna Due to Wind Disturbances, pp. 109–134.  
See Gawronski, W.
- Hinedi, S.**
- 42-106 The Advanced Receiver II Telemetry Test Results at Goldstone, pp. 119–131.  
See Sadr, R.
- 42-106 Symbol Lock Detection in the ARX II and Block V Receivers, pp. 132–154.  
See Shihabi, M.
- Hizlan, M.**
- 42-107 Determinate-State Convolutional Codes, pp. 36–56.  
See Collins, O.
- Issa, T. N.**
- 42-106 Stochastic Availability Analysis of Operational Data Systems in the Deep Space Network, pp. 394–403.
- Kahn, R.**
- 42-108 Position Determination of a Lander and Rover at Mars With Earth-Based Differential Tracking, pp. 279–293.  
W. M. Folkner, C. D. Edwards, and A. Vijayaraghavan
- Kelley, M. J.**
- 42-108 An Assembly to Provide a Time Reference for the JPL Network Operations Control Center, Real-Time, pp. 214–221.  
See Clements, P. A.
- Kent, S. S.**
- 42-106 A Carrier-Arraying Demonstration at Goldstone for Receiving Pioneer 11 Signals, pp. 307–334.  
See Pham, T. T.
- Kursinski, E. R.**
- 42-105 Radio Science Ground Data System for the Voyager–Neptune Encounter—Part I, pp. 109–127.  
S. Asmar
- Lam, B.**
- 42-106 Design and Status of the RF-Digitizer Integrated Circuit, pp. 155–159.  
See Rayhren, B.
- Lanagan, M.**
- 42-106 Performance of a High  $T_c$  Superconducting Ultra-Low Loss Microwave Stripline Filter, pp. 60–65.  
See Bautista, J. J.
- Lee, P.**
- 42-106 Wideband Waveguide Polarizer Development for SETI, pp. 384–393.  
P. H. Stanton
- Levy, R.**
- 42-105 Computation of Vibration Mode Elastic-Rigid and Effective Weight Coefficients From Finite-Element Computer Program Output, pp. 13–20.  
42-106 Algorithms for Structural Natural-Frequency Design, pp. 23–29.
- Lin, C. Y.**
- 42-108 Software-Engineering Process Simulation Model (SEPS), pp. 165–185.  
T. Abdel-Hamid and J. S. Sherif
- Lindqwister, U. J.**
- 42-108 A Demonstration of Centimeter-Level Monitoring of Polar Motion With the Global Positioning System, pp. 1–9.  
A. P. Freedman and G. Blewitt

- Lopez, J. G.**
- 42-108 An Assembly to Provide a Time Reference for the JPL Network Operations Control Center, Real-Time, pp. 214–221.  
See Clements, P. A.
- Maleki, L.**
- 42-108 A High-Performance Hg<sup>+</sup> Trapped Ion Frequency Standard, pp. 10–18.  
See Prestage, J. D.
- Matousek, S. E.**
- 42-107 Trajectory and Navigation System Design for Robotic and Piloted Missions to Mars, pp. 113–131.  
See Thurman, S. W.
- McEliece, R. J.**
- 42-105 Modifications of the Griesmer Bound, pp. 41–44.  
G. Solomon
- 42-107 Some Partial-Unit-Memory Convolutional Codes, pp. 57–72.  
See Abdel-Ghaffar, K.
- Mellstrom, J. A.**
- 42-105 Elevation Control System Model for the DSS 13 Antenna, pp. 83–108.  
See Gawronski, W.
- 42-106 Modeling and Simulations of the DSS 13 Antenna Control System, pp. 205–248.  
See Gawronski, W.
- 42-106 Pattern-Recognition Techniques Applied to Performance Monitoring of the DSS 13 34-Meter Antenna Control Assembly, pp. 30–51.  
P. Smyth
- 42-108 Real-Time Antenna Fault Diagnosis Experiments at DSS 13, pp. 96–108.  
C. Pierson and P. Smyth
- Mizuhara, A.**
- 42-108 250-kW CW Klystron Amplifier for Planetary Radar, pp. 201–213.  
See Cormier, R.
- Monk, A. M.**
- 42-106 Carrier-to-Noise Power Estimation for the Block V Receiver, pp. 353–363.
- Mueller, R. O.**
- 42-105 Design and Analysis of a Low-Loss Linear Analog Phase Modulator for Deep Space Spacecraft X-Band Transponder Applications, pp. 136–145.  
See Mysoor, N. R.
- Mysoor, N. R.**
- 42-105 Design and Analysis of a Low-Loss Linear Analog Phase Modulator for Deep Space Spacecraft X-Band Transponder Applications, pp. 136–145.  
R. O. Mueller
- Onyszchuk, I. M.**
- 42-106 Coding Gains and Error Rates From the Big Viterbi Decoder, pp. 170–174.
- 42-106 Testing Interconnected VLSI Circuits in the Big Viterbi Decoder, pp. 175–182.
- Ortiz, G. G.**
- 42-106 A Cooled 1- to 2-GHz Balanced HEMT Amplifier, pp. 52–59.  
S. Padin
- 42-106 Performance of a High  $T_c$  Superconducting Ultra-Low Loss Microwave Stripline Filter, pp. 60–65.  
See Bautista, J. J.
- Otoshi, T. Y.**
- 42-105 A Portable X-Band Front-End Test Package for Beam-Waveguide Antenna Performance Evaluation—Part II: Tests on the Antenna, pp. 54–68.  
S. R. Stewart and M. M. Franco

- Pham, T. T.**
- 42-106 A Portable Ka-Band Front-End Test Package for Beam-Waveguide Antenna Performance Evaluation—Part I: Design and Ground Tests, pp. 249–265.  
S. R. Stewart and M. M. Franco
- 42-106 A Portable Ka-Band Front-End Test Package for Beam-Waveguide Antenna Performance Evaluation—Part II: Tests on the Antenna, pp. 266–282.  
S. R. Stewart and M. M. Franco
- 42-106 Efficiency Calibration of the DSS 13 34-Meter Diameter Beam Waveguide Antenna at 8.45 and 32 GHz, pp. 283–297.  
See Slobin, S. D.
- 42-107 A Portable Ku-Band Front-End Test Package for Beam-Waveguide Antenna Performance Evaluation, pp. 73–80.  
S. R. Stewart and M. M. Franco
- 42-107 A Proposed Far-Field Method for Frequency-Stability Measurements on the DSS-13 Beam-Waveguide Antenna, pp. 81–87.
- 42-108 The Electrical Conductivities of the DSS-13 Beam-Waveguide Antenna Shroud Material and Other Antenna Reflector Surface Materials, pp. 154–164.  
M. M. Franco and H. F. Reilly, Jr.
- Pierson, C.**
- 42-108 Real-Time Antenna Fault Diagnosis Experiments at DSS 13, pp. 96–108.  
See Mellstrom, J.
- Pollara, F.**
- 42-105 Integer Cosine Transform for Image Compression, pp. 45–53.  
See Cheung, K.-M.
- Posner, E. C.**
- 42-107 Expected Antenna Utilization and Overload, pp. 104–112.
- Prestage, J. D.**
- 42-108 A High-Performance Hg<sup>+</sup> Trapped Ion Frequency Standard, pp. 10–18.  
R. L. Tjoelker, G. J. Dick, and L. Maleki
- Padin, S.**
- 42-106 A Cooled 1- to 2-GHz Balanced HEMT Amplifier, pp. 52–59.  
See Ortiz, G. G.
- Peng, T. K.**
- 42-106 A Carrier-Arraying Demonstration at Goldstone for Receiving Pioneer 11 Signals, pp. 307–334.  
See Pham, T. T.
- Petty, S.**
- 42-108 DSN  $G/T_{op}$  and Telecommunications System Performance, pp. 271–278.  
See Stelzried, C.
- Rafferty, W.**
- 42-108 DSN  $G/T_{op}$  and Telecommunications System Performance, pp. 271–278.  
See Stelzried, C.
- Randolph, L. W.**
- 42-105 Orbital Debris Radar Instrumentation, pp. 146–148.  
See Goldstein, R. M.
- Rayhrer, B.**
- 42-106 Design and Status of the RF-Digitizer Integrated Circuit, pp. 155–159.  
B. Lam, L. E. Young, J. M. Srinivasan, and J. B. Thomas

- Reilly, H. R., Jr.**
- 42-107 The L/C-Band Feed Design for the DSS 14 70-Meter Antenna (Phobos Mission), pp. 88–95.  
See Stanton, P. H.
- 42-108 The Electrical Conductivities of the DSS-13 Beam-Waveguide Antenna Shroud Material and Other Antenna Reflector Surface Materials, pp. 154–164.  
See Otoshi, T. Y.
- Remer, D. S.**
- 42-106 Modeling Preparation Costs for Space Missions by Using Major Cost Drivers, pp. 404–415.  
See Sherif, J. S.
- Rinker, G. C.**
- 42-108 The X-Windows Interactive Navigation Data Editor, pp. 66–78.
- Rochblatt, D. J.**
- 42-108 A Microwave Holography Methodology for Diagnostics and Performance Improvement for Large Reflector Antennas, pp. 235–252.
- 42-108 Performance Improvement of DSS-13 34-Meter Beam-Waveguide Antenna Using the JPL Microwave Holography Methodology, pp. 253–270.  
B. L. Seidel
- Rogstad, D. H.**
- 42-107 Suppressed Carrier Full-Spectrum Combining, pp. 12–20.
- Sadr, R.**
- 42-106 The Advanced Receiver II Telemetry Test Results at Goldstone, pp. 119–131.  
R. Bevan and S. Hinedi
- Schwartz, J. A.**
- 42-106 Design and Testing of an Active Quenching Circuit for an Avalanche Photodiode Photon Detector, pp. 102–110.  
See Arbel, D.
- Seidel, B. L.**
- 42-108 Performance Improvement of DSS-13 34-Meter Beam-Waveguide Antenna Using the JPL Microwave Holography Methodology, pp. 253–270.  
See Rochblatt, D. J.
- Shah, B.**
- 42-106 Symbol Lock Detection in the ARX II and Block V Receivers, pp. 132–154.  
See Shihabi, M.
- Shahshahani, M.**
- 42-105 Integer Cosine Transform for Image Compression, pp. 45–53.  
See Cheung, K.-M.
- 42-107 A Comparison of the Fractal and JPEG Algorithms, pp. 21–26.  
See Cheung, K.-M.
- Shaik, K.**
- 42-106 Spectral Filters for Laser Communications, pp. 93–101.
- Shell, J.**
- 42-106 Equivalent Circuit Model of Traveling-Wave Maser Slow-Wave Structures, pp. 66–92.
- Sherif, J. S.**
- 42-106 Modeling Preparation Costs for Space Missions by Using Major Cost Drivers, pp. 404–415.  
D. S. Remer and H. R. Buchanan

- 42-108 Software-Engineering Process Simulation Model (SEPS), pp. 165-185.  
See Lin, C. Y.
- Shihabi, M.**
- 42-106 Symbol Lock Detection in the ARX II and Block V Receivers, pp. 132-154.  
S. Hinedi and B. Shah
- Simon, M. K.**
- 42-106 A Carrier-Arraying Demonstration at Goldstone for Receiving Pioneer 11 Signals, pp. 307-334.  
See Pham, T. T.
- Slobin, S. D.**
- 42-106 Efficiency Calibration of the DSS 13 34-Meter Diameter Beam Waveguide Antenna at 8.45 and 32 GHz, pp. 283-297.  
T. Y. Otoshi, M. J. Britcliffe, L. S. Alvarez, S. R. Stewart, and M. M. Franco
- Smyth, P.**
- 42-106 Pattern-Recognition Techniques Applied to Performance Monitoring of the DSS 13 34-Meter Antenna Control Assembly, pp. 30-51.  
See Mellstrom, J.
- 42-108 Real-Time Antenna Fault Diagnosis Experiments at DSS 13, pp. 96-108.  
See Mellstrom, J.
- Solomon, G.**
- 42-105 Modifications of the Griesmer Bound, pp. 41-44.  
See McEliece, R. J.
- 42-107 Some Partial-Unit-Memory Convolutional Codes, pp. 57-72.  
See Abdel-Ghaffar, K.
- 42-108 Nonlinear, Nonbinary Cyclic Group Codes, pp. 84-95
- Sovers, O. J.**
- 42-106 JPL 1990-3: A 5-nrad Extragalactic Source Catalog Based on Combined Radio Interferometric Observations, pp. 364-383.
- Sridhar, S.**
- 42-106 Performance of a High  $T_c$  Superconducting Ultra-Low Loss Microwave Stripline Filter, pp. 60-65.  
See Bautista, J. J.
- Srinivasan, J. M.**
- 42-106 Design and Status of the RF-Digitizer Integrated Circuit, pp. 155-159.  
See Rayhrer, B.
- Stanton, P. H.**
- 42-106 Wideband Waveguide Polarizer Development for SETI, pp. 384-393.  
See Lee, P.
- 42-107 The L/C-Band Feed Design for the DSS 14 70-Meter Antenna (Phobos Mission), pp. 88-95.  
H. R. Reilly, Jr.
- Stelzried, C.**
- 42-108 DSN  $G/T_{op}$  and Telecommunications System Performance, pp. 271-278.  
R. Clauss, W. Rafferty, and S. Petty
- Stewart, S. R.**
- 42-105 A Portable X-Band Front-End Test Package for Beam-Waveguide Antenna Performance Evaluation—Part II: Tests on the Antenna, pp. 54-68.  
See Otoshi, T. Y.
- 42-106 A Portable Ka-Band Front-End Test Package for Beam-Waveguide Antenna Performance Evaluation—Part I: Design and Ground Tests, pp. 249-265.  
See Otoshi, T. Y.

42-106	A Portable Ka-Band Front-End Test Package for Beam-Waveguide Antenna Performance Evaluation—Part II: Tests on the Antenna, pp. 266–282.	42-108	Orbit-Determination Performance of Doppler Data for Interplanetary Cruise Trajectories, Part I: Error Analysis Methodology, pp. 31–48.
	See Otoshi, T. Y.		See Ulvestad, J. S.
42-106	Efficiency Calibration of the DSS 13 34-Meter Diameter Beam Waveguide Antenna at 8.45 and 32 GHz, pp. 283–297.	Tjoelker, R. L.	
	See Slobin, S. D.	42-108	A High-Performance Hg <sup>+</sup> Trapped Ion Frequency Standard, pp. 10–18.
42-107	A Portable Ku-Band Front-End Test Package for Beam-Waveguide Antenna Performance Evaluation, pp. 73–80.		See Prestage, J. D.
	See Otoshi, T. Y.	Ulvestad, J. S.	
42-108	DSS-13 Beam-Waveguide Antenna Performance in the Bypass Mode, pp. 135–153.	42-105	Phasing the Very Large Array on Galileo in the Presence of Jupiter's Strong Radio Emission, pp. 69–82.
42-108	Performance Improvement of DSS-13 34-Meter Beam-Waveguide Antenna Using the JPL Microwave Holography Methodology (Appendix)	42-108	Orbit-Determination Performance of Doppler Data for Interplanetary Cruise Trajectories, Part I: Error Analysis Methodology, pp. 31–48.
	See Rochblatt, D. J.		S. W. Thurman
Swanson, L.		42-108	Orbit-Determination Performance of Doppler Data for Interplanetary Cruise Trajectories, Part II: 8.4-GHz Performance and Data-Weighting Strategies, pp. 31–48.
42-106	Frame Error Rate of the NASA Concatenated Coding System, pp. 183–187.	K.-M. Cheung	Veruttipong, W.
42-108	Node Synchronization Schemes for the Big Viterbi Decoder, pp. 186–200.	42-105	Gaussian Beam and Physical Optics Iteration Technique for Wideband Beam Waveguide Feed Design, pp. 128–135.
	See Cheung, K.-M.		J. C. Chen and D. A. Bathker
Thomas, J. B.		Vijayaraghavan, A.	
42-106	Design and Status of the RF-Digitizer Integrated Circuit, pp. 155–159.	42-108	Position Determination of a Lander and Rover at Mars With Earth-Based Differential Tracking, pp. 279–293.
	See Rayhrer, B.		See Kahn, R. D.
Thurman, S. W.		Vilnrotter, V. A.	
42-107	Trajectory and Navigation System Design for Robotic and Piloted Missions to Mars, pp. 113–131.	42-106	Channel Assignments and Array Gain Bounds for the Ka-Band Array Feed Compensation System, pp. 160–169.
	S. E. Matousek		

**Wang, R. T.**

- 42-107 A Receiver Design for the Superconducting Cavity-Maser Oscillator, pp. 1-11.

G. J. Dick

**Young, L. E.**

- 42-106 Design and Status of the RF-Digitizer Integrated Circuit, pp. 155-159.

See Rayhrer, B.

**Weller, R.**

- 42-106 A Carrier-Arraying Demonstration at Goldstone for Receiving Pioneer 11 Signals, pp. 307-334.

See Pham, T. T.

**Zahopoulos, C.**

- 42-106 Performance of a High  $T_c$  Superconducting Ultra-Low Loss Microwave Stripline Filter, pp. 60-65.

See Bautista, J. J.

**Yan, T.-Y.**

- 42-106 Analysis of a Multiple Reception Model for Processing Images From the Solid-State Imaging Camera, pp. 111-118.

**Zimmerman, G. A.**

- 42-107 A 640-MHz 32-Megachannel Real-Time Polyphase-FFT Spectrum Analyzer, pp. 132-140.

M. F. Garyantes, M. J. Grimm, and B. Charny

- 42-107 Polyphase-Discrete Fourier Transform Spectrum Analysis for the Search for Extraterrestrial Intelligence Sky Survey, pp. 141-154.

S. Gulkis